



246 Socket, reducing, ISO/EN M4

ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations. Steel parts are hexagonal instead of beaded at the end no. 1.

EN		Dim. (1-2) [inch]	Code	a [mm]	s [mm]	z [mm]
ST_	B	¼ - ⅛	770 246 115	32	17	22
ST_	G	¼ - ⅛	770 246 215	32	17	22
ST_	B	⅜ - ¼	770 246 116	35	22	25
ST_	G	⅜ - ¼	770 246 216	35	22	25
•	B	½ - ¼	770 246 117	43		30
		½ - ¼	770 246 217	43		30
•	B	½ - ⅜	770 246 118	43		30
		½ - ⅜	770 246 218	43		30
•	B	¾ - ⅜	770 246 119	48		33
		¾ - ⅜	770 246 219	48		33
•	B	¾ - ½	770 246 120	48		33
		¾ - ½	770 246 220	48		33
•	B	1 - ½	770 246 121	55		38
		½	770 246 221	55		38
•	B	1 - ¾	770 246 122	55		38
		¾	770 246 222	55		38
-	B	1 ¼ - ½	770 246 123	60		41
		¼ - ½	770 246 223	60		41
•	B	1 ¼ - ¾	770 246 124	60		41
		¼ - ¾	770 246 224	60		41
•	B	1 ¼ - 1	770 246 125	60		41
		¼ - 1	770 246 225	60		41
-	B	1 ½ - ¾	770 246 126	60		41
		½ - ¾	770 246 226	60		41
•	B	1 ½ - 1	770 246 127	63		44
		½ - 1	770 246 227	63		44
•	B	1 ½ - 1 ¼	770 246 128	63		44
		½ - 1 ¼	770 246 228	63		44
-	B	2 - 1	770 246 129	70		46
•	B	2 - 1 ¼	770 246 130	70		46
		¼	770 246 230	70		46
•	B	2 - 1 ½	770 246 131	70		46
		½	770 246 231	70		46
-	B	2 ½ - 1 ½	770 246 132	83		56
		½ - 1 ½	770 246 232	83		56
-	B	2 ½ - 2	770 246 133	80		53
		½ - 2	770 246 233	80		53
-	B	3 - 2	770 246 134	87		57
-	B	3 - 2 ½	770 246 135	91		61
		½	770 246 235	91		61